



K30 / K30L



EXTRA LOW PROFILE LIFT FOR CARS

Capacity 3000 kg

MODEL : K30 / K30L



Description

Extra low rise electrohydraulic lift with min. travel 96mm and double platform. Platforms connected by double torsion beam for perfect synchronicity and levelling.

Double redundant hydraulic circuit with 4 pistons, 2 on each platform, with safety and shut-off valve on the hydraulic circuit for overload protection and hoses breaks. Self-lubricating axle bearings on each rotating pin, no maintenance required, High-sliding and self-lubricating polyethylene sliding pads. Lowering speed control with compensation valve. "Hold to run" 24V Control. Electric Micro Switch with "foot guard" device and acoustic signal, to protect the last lowering travel. Suitable for both floor and recessed installation, even under difficult conditions in case of not available deep pits.

Made in Italy – Made in LV8 ELEVATE
Via A. Novella, 46, 43058 Sorbolo (PR), Italy
PH.: +39 0522 687907 – FAX: +39 0522 684498 E-MAIL: info@lv8.it
www.lv8elevate.it

Technical data

- Electro-hydraulic Control Unit in metal structure (without plastic parts)
- Capacity 3000 kg
- Power Unit Kw 1,1 400V 3Ph 50Hz
- Total Weight 500kg
- Lifting height min. 95mm max. 960 mm
- Up-Down Travel speed 20/20sec

Standard equipment

- 4 flap run- up ramps
- Hoses covered with anti-blast sheath
- Kit of 4 rubber pads h 20mm

Optional

- Rubber pads h 40mm
- Rubber pads h 60mm
- Additional run-up ramps for racing/super sport vehicles
- Kit for built-in central cover
- Kit for recessed frame
- Kit for built-in slides for horizontal standing ramps position
- Hose extension
- Additional crossbars for vehicles
- Single-Phase motor
- Basement and-or platform hot zinc-coating process
- Ral colors on request

Technical Drawing

